



The Leading Ones

Generator RL/RLH

Ultrasonic welding generator 35 kHz / 20 kHz

The ultrasonic welding generator RL is suitable for the operation of the ultrasonic welding machine MP2021 as well as for the relevant oscillator systems.





- . RLH with TIM5 controller for increased power
- . Easy to program
- . Multitrack for the synchronous operation of several modules optionally available
- . Separate item counter for RLH

Specification RL/RLH

Operating frequency:	35 kHz / 20 kHz	
Maximum power output:	RL35:	250 / 400 / 600 / 900 W
	RL20:	1500 W
	RLH20:	3000 W
Power supplies:	$\pm 10\%$:	230 V, 50 / 60 Hz 200 V, 50 / 60 Hz 110 V, 50 / 60 Hz (only for 250 / 400 / 600 W)
Operating modes:	Time dependant, Contact cut-off	
Data input:	With encoder keys	
Dimensions WxHxD:	RL:	135 x 280 x 400 mm, without connector
	RLH:	260 x 280 x 400 mm, without connector
Weight:	RL:	7 kg
	RLH:	16 kg

Additional technical information available on request.



RINCO ULTRASONICS AG
 CH-8590 Romanshorn 1
 Tel. +41 71 466 41 00
 Fax +41 71 466 41 01
 info@rincoultrasonics.com
 www.rincoultrasonics.com