



The Strong Ones



# MP 702

**Ultrasonic welding machine 70 kHz**

The ultrasonic welding machine MP702 is suitable for welding operations of very small thermoplastic parts.





- . Configurable with SL generators
- . Simple tool change and quick setup
- . Modular construction
- . Designed for the assembly into special purpose machines
- . Ideal for the welding of monofilaments and multifilaments

## Specification MP702

Operating frequency:	<b>70 kHz</b>
Safety:	This ultrasonic welding machine conforms to <b>CE</b> standards and thus corresponds to the European safety requirements
Switches:	Two-hand start. EMERGENCY STOP is at the front
Drive type:	Pneumatic double acting cylinder Ø 12 mm
Drive energy:	Compressed air supply: 7 bar maximum 6 bar nominal Maximum consumption at 6 bar: approx. 0.02 lt.n/stroke
Maximum force:	60 N at 6 bar compressed air
Maximum stroke:	40 mm
Weight:	9 kg without generator
Throat depth:	102 mm from the centre line of the horn to the column
Height adjustment:	240 mm using height adjusting mechanism
Generator:	<b>SL70-100</b>

Additional technical information available on request.



**RINCO ULTRASONICS AG**  
 CH-8590 Romanshorn 1  
 Tel. +41 71 466 41 00  
 Fax +41 71 466 41 01  
 info@rincoultrasonics.com  
 www.rincoultrasonics.com